



VS 05

The Unrivaled Leader of Efficiency

The premier product of the Vivid Series, the **Vivid Signature** was constructed with unparalleled solar heat rejection, implementing the most ideal atmosphere for whenever you are on the road.

SPECIFICATIONS	
Visible Light Transmission	5 %
Visible Light Reflection (Int) / (Ext)	6%/7%
UV Rejection	99 %
IR Rejection	97 %
Solar Heat Gain Coefficient	0.28
Shading Coefficient	0.42
Total Solar Energy Rejection	72 %

*Thickness: 2 Mil



























VS 15

The Unrivaled Leader of Efficiency

The premier product of the Vivid Series, the **Vivid Signature** was constructed with unparalleled solar heat rejection, implementing the most ideal atmosphere for whenever you are on the road.

SPECIFICATIONS	
Visible Light Transmission	15 %
Visible Light Reflection (Int) / (Ext)	6%/7%
UV Rejection	99 %
IR Rejection	97 %
Solar Heat Gain Coefficient	0.30
Shading Coefficient	0.44
Total Solar Energy Rejection	70 %

*Thickness: 2 Mil



























VS 25

The Unrivaled Leader of Efficiency

The premier product of the Vivid Series, the **Vivid Signature** was constructed with unparalleled solar heat rejection, implementing the most ideal atmosphere for whenever you are on the road.

SPECIFICATIONS	
Visible Light Transmission	25 %
Visible Light Reflection (Int) / (Ext)	6%/8%
UV Rejection	99 %
IR Rejection	97 %
Solar Heat Gain Coefficient	0.35
Shading Coefficient	0.48
Total Solar Energy Rejection	65 %

*Thickness: 2 Mil




























VS 35

The Unrivaled Leader of Efficiency

The premier product of the Vivid Series, the **Vivid Signature** was constructed with unparalleled solar heat rejection, implementing the most ideal atmosphere for whenever you are on the road.

SPECIFICATIONS	
Visible Light Transmission	35 %
Visible Light Reflection (Int) / (Ext)	7%/8%
UV Rejection	99 %
IR Rejection	97 %
Solar Heat Gain Coefficient	0.38
Shading Coefficient	0.51
Total Solar Energy Rejection	62 %

*Thickness: 2 Mil



























VS 50

The Unrivaled Leader of Efficiency

The premier product of the Vivid Series, the **Vivid Signature** was constructed with unparalleled solar heat rejection, implementing the most ideal atmosphere for whenever you are on the road.

SPECIFICATIONS	
Visible Light Transmission	50 %
Visible Light Reflection (Int) / (Ext)	8%/9%
UV Rejection	99 %
IR Rejection	97 %
Solar Heat Gain Coefficient	0.43
Shading Coefficient	0.56
Total Solar Energy Rejection	57 %

*Thickness: 2 Mil



























VS70

The Unrivaled Leader of Efficiency

The premier product of the Vivid Series, the **Vivid Signature** was constructed with unparalleled solar heat rejection, implementing the most ideal atmosphere for whenever you are on the road.

SPECIFICATIONS	
Visible Light Transmission	74 %
Visible Light Reflection (Int) / (Ext)	8%/9%
UV Rejection	99 %
IR Rejection	81%
Solar Heat Gain Coefficient	0.60
Shading Coefficient	0.74
Total Solar Energy Rejection	40 %

*Thickness: 2 Mil




























VS 80

The Unrivaled Leader of Efficiency

The premier product of the Vivid Series, the **Vivid Signature** was constructed with unparalleled solar heat rejection, implementing the most ideal atmosphere for whenever you are on the road.

SPECIFICATIONS	
Visible Light Transmission	84 %
Visible Light Reflection (Int) / (Ext)	8? % / 9? %
UV Rejection	99 %
IR Rejection	71 %
Solar Heat Gain Coefficient	0.60?
Shading Coefficient	0.74?
Total Solar Energy Rejection	30 %

*Thickness: 2 Mil





















