

# Technical Data Sheet



## Paint Protection Film

# XP LIGHT STONE

### Information


**ULTRAFIT XP LIGHT STONE** is a high performance, self-adhesive, hydrophobic polyurethane film designed to protect automotive paint from harmful effects of stone chips and abrasion. It is a high-end light gray PPF with a subtle earthy-green undertone, mirroring the natural tones of real stone, while exuding refined elegance and durability.

Recommended Shelf Life 2 years from date of purchase\*  
Recommended Storage Conditions 72°F (22°C) @ 50% RH

### Characteristics

- Color Gloss
- Hydrophobicity
- Shock absorbent
- Self-Heal

### Product Structure



#### Layer Descriptions

**TPU** Impact-resistance

**Product Thickness** 9mil

PROPERTIES		TYPICAL VALUES	STANDARDS USED
Peel Adhesion		2000±500 gf / inch	ASTM D3330
Tensile Elongation @ Break		195±20 %	ASTM D882
Water Surface Contact Angle		90±10 °	.
Gravelometer		PASS	ASTM D3170
Outdoor Weathering (dE*ab, 1000hr)	Q-UV	<1 %	ASTM G154
	Q-SUN	<1 %	ASTM G155

\* If installing film after recommended shelf-life, re-certification by ULTRAFIT is required.

#### Notice

The performance representations and suitability for use described in this Technical Data Sheet are intended as a guide only. Since the specific conditions of product use are known only to the user, it is the user's responsibility to determine whether the product is suitable its intended application.