Technical Data Sheet

Paint Protection Film

ULTRAFIT™

XP MOONLIGHT

Information

ULTRAFIT XP MOONLIGHT is a high performance, self-adhesive, hydrophobic polyurethane film designed to protect automotive paint from harmful effects of stone chips and abrasion. It enhances style with a touch of subtle charisma and sophistication.

Recommended Shelf Life 2 years from date of purchase*
Recommended Storage Conditions 72℉ (22℃) @ 50% RH

Characteristics

- Transfer Headlight
- Hydrophobicity
- Shock absorbent
- Self-Heal

Product Structure



Layer Descriptions

TPU Impact-resistance

Product Thickness 8mil

PROPERTIES		TYPICAL VALUES	STANDARD
Peel Adhesion		1.7 ± 0.4 kg/in² (30 min) 2.0 ± 0.5 kg/in² (1 hr)	ASTM D3330
Gloss		>80 ± 2	ISO 2813
Haze		<1 ± 0.1%	ASTM D-1003
Tensile Strength		5,000 ± 250 psi 34.47 ± 2 MPa	ASTM D-412
Elongation		>200	ASTM D-412
Durability		ΔE ≤ 2 (1,000 hr)	ASTM G154
Q-UV	UVA Bulb	<1% <1%	8 hours 50℃ UV exposure 4 hours 60℃ condensation

* If installing film after recommended shelf-life, re-certification by ULTRAFIT is required.

Notice

The performance representations and suitability for use described in this Technical Data Sheet are intended as a guide only. Since the specific conditions of product use are known only to the user, it is the user's responsibility to determine whether the product is suitable its intended application.